

**SAFETY DATA SHEET**

REVISION DATE: 07-23-2015

SUPERSEDES: 03-26-2015

**SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER****PRODUCT INFORMATION**

PRODUCT: FOSTER 90-66CA PART A  
PRODUCT DESCRIPTION: Sealer/coating  
INTENDED USE: Adhesive  
PRODUCT IDENTIFIER: 829494PM

**COMPANY INFORMATION**

H.B. Fuller Company  
1200 Willow Lake Boulevard  
Vadnais Heights, MN 55110  
Telephone: 888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS Hazard  
Symbols:**



**GHS Signal Word:** Danger

**GHS Classification:** Germ Cell Mutagenicity Category 1B; Carcinogenicity Category 1B; Skin Corrosion/Irritation Category 2; Reproductive Toxicity Category 2; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2; Hazardous to the aquatic environment - Acute Category 2; Flammable Liquid Category 3; Hazardous to the aquatic environment - Chronic Category 3

**GHS Hazard Phrases:** Flammable liquid and vapour.; Causes skin irritation.; May cause genetic defects.; May cause cancer.; Suspected of damaging fertility or the unborn child.; May cause damage to organs through prolonged or repeated exposure.; Toxic to aquatic life.; Harmful to aquatic life with long lasting effects.

**GHS Precautions:**

**Safety Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.

Print Date: 07-24-2015

FOSTER 90-66CA PART A  
829494PM**SAFETY DATA SHEET**

**Storage:** Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS #	PERCENT	Classification	Note
Carbon black	1333-86-4	30 - 50	Carc. 2; H351	*(see below)
Aromatic petroleum distillate	64742-95-6	10 - 30	Asp. Tox. 1; H304 Carc. 1B; H350 Muta. 1B; H340	
Toluene	108-88-3	10 - 30	Asp. Tox. 1; H304 Acute Tox. 4; H302 Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H336	
Trimethylbenzene, 1,2,4-	95-63-6	5 - 10	Aquatic Chronic 2; H411 Acute Tox. 4; H332 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335	
Polybutene	9003-29-6	1 - 5	Aquatic Chronic 4; H413	
Quinone dioxime, para	105-11-3	1 - 5	Acute Tox. 4; H332 Acute Tox. 4; H302	
Diethylbenzene	25340-17-4	0.1 - 1	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Asp. Tox. 1; H304 Flam. Liq. 2; H225 Skin Irrit. 2; H315	

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**IF INHALED:** Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

**IF SWALLOWED:** Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**SAFETY DATA SHEET**
**SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Vapors are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide Nitrogen containing gases

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

SPECIAL PROTECTION:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.
METHODS FOR CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

Handling:	Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Keep away from heat, sparks and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapor and product residue. Observe all labeled precautions until container is cleaned. Drums of this material should be grounded when pouring. <b>DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.</b>
-----------	---

Storage: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**
**EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Carbon black	* (see below)	3 mg/m <sup>3</sup> TWA (inhalable fraction)	3.5 mg/m <sup>3</sup> TWA
Toluene		20 ppm TWA	200 ppm TWA 300 ppm Ceiling
Xylene		100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m <sup>3</sup> TWA

**SAFETY DATA SHEET**

Cumene		50 ppm TWA	50 ppm TWA; 245 mg/m <sup>3</sup> TWA Skin absorption may potentially contribute to the overall exposure to this material.
--------	--	------------	---

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

**ENGINEERING CONTROL METHODS:**

<b>VENTILATION:</b>	Use local exhaust ventilation or other engineering controls to minimize exposures.
<b>EYE PROTECTION:</b>	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
<b>SKIN PROTECTION:</b>	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.
<b>GLOVES:</b>	Nitrile
<b>RESPIRATORY PROTECTION:</b>	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>PHYSICAL STATE:</b>	Liquid
<b>COLOR:</b>	Black
<b>ODOR:</b>	Solvent
<b>ODOR THRESHOLD:</b>	Not established
<b>pH:</b>	Not established
<b>FREEZING/MELTING POINT (deg. C):</b>	Not established
<b>BOILING POINT (deg. C):</b>	Not established
<b>FLASH POINT:</b>	24C; 75F Pensky-Martens
<b>EVAPORATION RATE:</b>	Not established
<b>FLAMMABILITY:</b>	Not a flammable solid or gas
<b>UPPER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>LOWER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>VAPOR PRESSURE (mm Hg):</b>	Not established
<b>VAPOR DENSITY:</b>	Not established
<b>WEIGHT PER GALLON (lbs.):</b>	9.60
<b>SPECIFIC GRAVITY:</b>	1.150
<b>SOLUBILITY:</b>	Not established
<b>OCTANOL/WATER COEFFICIENT:</b>	Not established
<b>AUTOIGNITION TEMPERATURE:</b>	Not established
<b>DECOMPOSITION TEMPERATURE:</b>	Not established
<b>VISCOSITY:</b>	No data available.

Print Date: 07-24-2015

FOSTER 90-66CA PART A  
829494PM**SAFETY DATA SHEET**

---

SOLIDS (% by weight):	72.5
VOC, weight percent	27.70
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	318g/liter of material

**SECTION 10: STABILITY AND REACTIVITY**

---

---

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Nitrogen containing gases

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

---

**Component Toxicity / Toxicology Data:**

COMPONENT NAME	LD50/LC50
Aromatic petroleum distillate	INHALATION LC50-4H RAT 3,400.00 PPM DERMAL LD50 RABBIT > 2,000.00 MG/KG
Toluene	ORAL LD50 RAT 636 MG/KG INHALATION LC50-4H RAT 12.50 MG/L DERMAL LD50 RABBIT 8,390.00 MG/KG
Trimethylbenzene, 1,2,4-	ORAL LD50 RAT 3,400 MG/KG INHALATION LC50-4H RAT 18.00 G/M3 DERMAL LD50 RABBIT > 3,160.00 MG/KG

**This product is a mixture. Unless noted, the information below is based on components.**

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Eye contact may cause moderate to severe eye irritation. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a probable reproductive hazard based on human studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause drowsiness or dizziness. May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Lungs Reproductive system Liver Central nervous system Blood Kidneys

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Lung disease, Liver disease, Blood disorders (like anemia), Kidney disease

**SECTION 12: ECOLOGICAL INFORMATION**

---

---

**SAFETY DATA SHEET**

OVERVIEW:	No ecological information available for this product.
MOBILITY:	No data available.
PERSISTENCE:	No data available.
BIOACCUMULATION:	No data available.

**This product has not been tested for ecological effects. Relevant information for components is listed below:**

Component:	Ecotoxicity values:
Aromatic petroleum distillate	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L <b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 6.14 mg/L <b>Acute Toxicity (Algae):</b> Not established
Toluene	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-through] (1 day old); 96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-static]; 96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static] <b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48 Hr EC50 Daphnia magna: 11.5 mg/L <b>Acute Toxicity (Algae):</b> 96 Hr EC50 Pseudokirchneriella subcapitata: >433 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static]
Trimethylbenzene, 1,2,4-	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through] <b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 6.14 mg/L <b>Acute Toxicity (Algae):</b> Not established

**SECTION 13: DISPOSAL CONSIDERATIONS**

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene Xylenes (o-, m-, p- isomers)

**SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT:	UN1139, COATING SOLUTION, 3, III
IATA:	UN1139, COATING SOLUTION, 3, III
IMDG:	UN1139, COATING SOLUTION, 3, III, FLASH POINT 27°C C.C., EMS F-E, S-E

**SECTION 15: REGULATORY INFORMATION**
**INVENTORY STATUS**

U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
CANADIAN CEPA DSL:	This product contains a component that is not on the DSL. If you are the importer of this product into Canada, contact H.B. Fuller for chemical tracking and notification information.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.
AUSTRALIA AICS:	This product is in compliance with the Australian Inventory of Chemical Substances requirements.

Print Date: 07-24-2015

FOSTER 90-66CA PART A  
829494PM**SAFETY DATA SHEET**

JAPAN ENCS: This product is in compliance with the Japanese Existing and New Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at [reg.request@hbfuller.com](mailto:reg.request@hbfuller.com) to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA: Phenol, 4-nitroso-  
40 CFR 721.10228

**FEDERAL REPORTING****EPA SARA Title III Section 313**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Toluene	108-88-3	10 - 30
1,2,4-Trimethylbenzene	95-63-6	5 - 10
Xylene (mixed isomers)	1330-20-7	0.1 - 1
Cumene	98-82-8	0.1 - 1

**STATE REPORTING****Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:**

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Carbon black (Carcinogen)	1333-86-4	30 - 50
Cumene (Carcinogen)	98-82-8	0.1 - 1
Toluene (Developmental toxin)	108-88-3	10 - 30
Benzene, methyl- (Female reproductive toxin)	108-88-3	10 - 30

**Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's.

**SECTION 16: OTHER INFORMATION**

SDS VERSION DATE: 07-23-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Print Date: 07-24-2015

FOSTER 90-66CA PART A  
829494PM**SAFETY DATA SHEET**

---

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.