

Material Safety Data Sheet

LEWCO 1650T

Teflon Impregnated Fiberglass Cloth

SECTION I

Manufacturer's Name: LEWCO Specialty Products, Inc.
6859 Renoir Avenue
Baton Rouge, LA 70806
(800) 221-6414 TX & AR (800) 233-9755
(225) 924-3221 Fax (225) 927-2918

General Description: Polytetrafluoroethylene coated fiberglass fabric

Trade Name: LEWCO 1650 T

SECTION II –Ingredients

Polytetrafluoroethylene	16 %
Fiberglass Fabric	80 %
Titanium Dioxide	4 %
Carbon	Trace

SECTION III – Health Hazard Data

Effects of Exposure: May be a skin irritant if product is severely damaged

First Aid Procedures: Wash affected area with soap and water

SECTION IV – Fire and Explosion Data

Autoignition point: 900 F

Extinguishing media: Water

No special fire fighting procedures required.

No unusual fire explosion hazards

SECTION V – Physical Data

Boiling Point: None
Specific Gravity: 2.5
Softening Point: Not applicable
Melting Point: Not applicable
Vapor Density: Not applicable
Percent Volatile: Not applicable
Evaporation Rate: Not applicable
Solubility in Water: Not applicable
Odor, Appearance and color: Odorless grey fabric

SECTION VI – Reactivity Data

Stability: Stable
Incompatibility (Material to avoid): Fabric strength is destroyed in strong bases and hydrofluoric acid.
Hazardous Decomposition or Byproducts: Traces of incompletely burned fluorocarbon products.
Hazardous Polymerization: Will not occur

SECTION VII – Spill and Disposal Procedures

Material can be brushed off, re-rolled and used.

Waster disposal procedure: Landfill in compliance with local, state and federal regulations.

SECTION VIII – Personnel Protection Information

Normal long sleeved work clothing and gloves should be worn.
Lifting devises may be needed for heavy rolls.
Wash work clothes separately from other clothing.

Issue Date: 2/1/92
Revised Date: 06/21/11

Prepared By: Jamie D Guzzardo