

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Fabrication Adhesive
- **Article number:** 88-70, 88-71
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesive.
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Mon-Eco Industries, Inc.
5 Joanna Ct.
East Brunswick, NJ 08816
Phone: 732-257-7942
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585



MON-ECO INDUSTRIES, INCORPORATED

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H317, H360Df, H411.
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).
The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H360.
Repr. 1 H360: May damage fertility or the unborn child



health hazard

Carc. 1B H350 May cause cancer.
Repr. 1B H360Df May damage the unborn child. Suspected of damaging fertility.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS


Printing date 20.03.2015

Revision: 20.03.2015


Trade name: Fabrication Adhesive

(Contd. of page 1)

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

 T; Toxic


R61: May cause harm to the unborn child.

 Xn; Harmful

R62: Possible risk of impaired fertility.

 Xi; Sensitising

R43: May cause sensitisation by skin contact.

 N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H317, H360Df, H411.

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H360.

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS07 GHS08 GHS09

- **Signal word** Danger

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 2)

- **Hazard-determining components of labelling:**

benzyl butyl phthalate

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Petroleum Distillates

- **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H317,H360Df, H411.

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H360.

H360: May damage fertility or the unborn child.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H360Df May damage the unborn child. Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P261 Avoid breathing mist/vapours/spray.

P281 Use personal protective equipment as required.

P273 Avoid release to the environment.

P264 Wash thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Restricted to professional users.

- **Hazard description:**

- **WHMIS-symbols:**

D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 0

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2

Fire = 0

Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 3)

· HMIS Long Term Health Hazard Substances








85-68-7 | benzyl butyl phthalate

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:






CAS: 85-68-7 EINECS: 201-622-7 Index number: 607-430-00-3	benzyl butyl phthalate   	10-25%
CAS: 78330-21-9	alcohols, C11-C14-iso, ethoxylated   	≤ 2,5%
	Petroleum Distillates 	< 1%

· SVHC

85-68-7 | benzyl butyl phthalate

- **Additional information:**
For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.
For the wording of the listed risk phrases refer to section 16.

· Notable Trace Components (≤ 0,1% w/w)

CAS: 55965-84-9 Index number: 613-167-00-5	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)     
---	---

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 4)

- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Provide oxygen treatment if affected person has difficulty breathing.
- **After skin contact:**
Immediately remove any clothing soiled by the product.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Coughing
Dizziness
Allergic reactions
Irritant to eyes.
Gastric or intestinal disorders when ingested.
Nausea in case of ingestion.
- **Hazards**
May cause cancer.
Suspected of damaging fertility or the unborn child.
- **4.3 Indication of any immediate medical attention and special treatment needed**
Medical supervision for at least 48 hours.
If necessary oxygen respiration treatment.
Treat skin and mucous membrane with antihistamine and corticoid preparations.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Water haze or fog
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** None.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 5)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Particular danger of slipping on leaked/spilled product.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Send for recovery or disposal in suitable receptacles.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Prevent formation of aerosols.
Use only in well ventilated areas.
Avoid splashes or spray in enclosed areas.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 6)

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Pregnant women should strictly avoid inhalation or skin contact.
- **Respiratory protection:**
Suitable respiratory protective device recommended.
Use suitable respiratory protective device when high concentrations are present.
Use suitable respiratory protective device when aerosol or mist is formed.
For spills, respiratory protection may be advisable.
NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No further relevant information available.
- **Risk management measures**
See Section 7 for additional information.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

No further relevant information available.

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid
Colour: Not determined.

· Odour: Mild

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: 100 °C (212 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Auto/Self-ignition temperature: Not determined.

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· Vapour pressure at 20 °C (68 °F): 23 hPa (17 mm Hg)

· Density at 20 °C (68 °F): 1,12 g/cm³ (9,346 lbs/gal)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

water: Dispersible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· 9.2 Other information: No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 8)

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions**
Toxic fumes may be released if heated above the decomposition point.
Reacts with strong acids and oxidising agents.
- **10.4 Conditions to avoid**
Keep away from heat and direct sunlight.
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect:**
- **on the skin:** Slight irritant effect on skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitisation:** Sensitisation possible through skin contact.
- **Subacute to chronic toxicity:** No further relevant information available.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Danger through skin adsorption.
- **Acute effects (acute toxicity, irritation and corrosivity):** Irritating to eyes.
- **Sensitisation:** May cause an allergic skin reaction.
- **Repeated dose toxicity:**
May cause damage to organs through prolonged or repeated exposure.
Repeated exposures may result in skin and/or respiratory sensitivity.
Suspected of damaging fertility or the unborn child.
May cause cancer.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
Carc. 1B, Repr. 1B

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** Toxic for aquatic organisms
- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 9)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT** Not Regulated
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

- **DOT** Not Regulated

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 10)

- ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (benzyl butyl phthalate)
- IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (benzyl butyl phthalate), MARINE POLLUTANT
- IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (benzyl butyl phthalate)

- 14.3 Transport hazard class(es)

- DOT
- Class Not Regulated

- ADR



- Class 9 (M6) Miscellaneous dangerous substances and articles.
- Label 9

- IMDG, IATA



- Class 9 Miscellaneous dangerous substances and articles.
- Label 9
- 14.4 Packing group
- DOT Not Regulated
- ADR, IMDG, IATA III
- 14.5 Environmental hazards: Product contains environmentally hazardous substances: benzyl butyl phthalate
- Marine pollutant: Yes
Symbol (fish and tree)
- Special marking (ADR): Symbol (fish and tree)
- Special marking (IATA): Symbol (fish and tree)
- 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles.
- Danger code (Kemler): 90
- EMS Number: F-A,S-F
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 11)

· Transport category	3
· Tunnel restriction code	E

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (benzyl butyl phthalate), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

Present in trace quantities.

75-07-0 acetaldehyde

50-00-0 formaldehyde

123-91-1 1,4-dioxane

108-10-1 4-methylpentan-2-one

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

Present in trace quantities: methanol, 4-methylpentan-2-one.

85-68-7 benzyl butyl phthalate

67-56-1 methanol

108-10-1 4-methylpentan-2-one

· Carcinogenic Categories

· EPA (Environmental Protection Agency)

85-68-7 benzyl butyl phthalate

C

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 12)

· IARC (International Agency for Research on Cancer)		
85-68-7	benzyl butyl phthalate	3

· TLV (Threshold Limit Value established by ACGIH)
None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients are listed.

· Canada
· Canadian Domestic Substances List (DSL)
All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)
None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)
85-68-7 benzyl butyl phthalate

· Other regulations, limitations and prohibitive regulations
This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· Substances of very high concern (SVHC) according to REACH, Article 57
85-68-7 benzyl butyl phthalate

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H350 May cause cancer.

H360Df May damage the unborn child. Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R61 May cause harm to the unborn child.

R62 Possible risk of impaired fertility.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 14)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 20.03.2015

Revision: 20.03.2015

Trade name: Fabrication Adhesive

(Contd. of page 13)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 1B: Carcinogenicity, Hazard Category 1B
Repr. 1B: Reproductive toxicity, Hazard Category 1B
Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com