

TECHNICAL INFO

Glass lagging tapes are designed to replace asbestos. Woven edge tape is available in thicknesses of 1/32", 1/16", 1/8" and 1/4" and widths from 1" to 12".

These tapes are used with fiberglass lagging cloth as an edging for seam sealing. They are also used as a replacement for asbestos tape in wrapping pipes for personnel protection. This tape meets government specs, MIL-C20079G, Type II HH-P-0031E (SH).



Application

- Pipe Wrapping
- Gasketing
- Expansion Joints
- Heat Shields
- OEM Applications
- Tadpole Tape

Specifications

Maximum service temperature: 1000°F

K Value (BTU-in./hr. sq. ft. Deg F.): 0.419

Fiber: DE yarns which are designed for maximum flexibility and non-irritating qualities.

All statements herein are expressions of opinion which we believe to be accurate and reliable but are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind, expressed or implied is made or intended.

Revised 1112

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



Innovative Insulation Systems

HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon OH 44139 | 440.914.1122

North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

California: 4113 Gold River Lane | Stockton, CA 95206 | 1.800.833.4500

Texas: 8905 Market Street | Houston, TX 77029 | 1.800.874.1748