

Description

488S is a pressure sensitive tape manufactured with a 1.5-mil aluminum foil backing and a performance adhesive system.

Applications

- 488S is used for sealing aluminum faced duct and pipe insulation systems.

Features and Benefits

- All Weather Formula adhesive system provides a durable long term bond
- Standard grade foil backing performs on the job site while offering cost efficiency to the contractor.
- Functions as a vapor barrier and assures integrity of the insulation system.
- Release liner provides easy removal for efficient application on the job site

<u>Physical Properties:</u>	<u>US Measurements</u>	<u>Metric</u>
Backing Type	Dead Soft Aluminum Foil	Dead Soft Aluminum Foil
Backing Thickness	1.5 mils	0.04 mm.
Adhesion to Steel	90.0 (oz./in. width)	25.02 n/25.4 mm.
Adhesive System	Rubber	Rubber
Elongation	3.0%	3.0%
Application Temp. Range	10° F to 180° F	-12.22° C to 82.22° C
Post Application Temp. Range	-10° F to 180° F	-23.33° C to 82.22° C
UL 723 Ratings	Flame Spread 10 Smoke Developed 5	Flame Spread 10 Smoke Developed 5

NOTE: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry, and free of grease, oil or other contaminants.

ITC – 7/2009