



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO Treated Fiberglass Fabric

Product Specifications

LEWCO Styles 1400 Z, 2100 Z, and 2800 Z are asbestos free and have been specially manufactured and coated with vermiculite to provide a higher temperature resistance in certain applications. This fabric works very well in welding curtain type applications. If this fabric is used for removable insulation jacketing against hot surfaces above 500°F, stainless steel blanket mesh is recommended due to considerable loss in tensile strength. Contact your LEWCO representative with your application.

Typical Properties

	<u>1400 Z</u>	<u>2100 Z</u>	<u>2800 Z</u>
Color	Gold	Gold	Gold
Weight (Oz./Sq.Yd.)	14.0	21.0	28.0
Thickness	.028"	.030"	.060"
Weave	Mod. Plain	Plain	Plain
Maximum Temperature	1500 ° F	1500 ° F	1500 ° F
Maximum Continuous Temperature	1100 ° F	1100 ° F	1100 ° F
Width	60"	60"	60"

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabricating and applying removable/reusable insulation, and with those working with elding curtains and fire blankets.
S2100Z-08/26/04Rev01MED