

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > For use on a variety of smooth substrates as a general purpose tape
- > Packaging, bundling, binding, holding, splicing & banding
- > Automotive harness marking

## ADVANTAGES AND BENEFITS

- > Available in 12 colors
- > Multiple uses for home, school, and industry

## CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Crepe paper

Adhesive: Rubber-based adhesive

## COLOR(S)

	Black (BLK)		Red (RED)		Orange (ORG)
	White (WHI)		Light Blue (LBL)		Purple (PUR)
	Yellow (YEL)		Light Green (LGR)		Pink (PNK)
	Blue (BLU)		Dark Green (DGR)		



## STANDARD WIDTH(S)

12 mm    18 mm    24 mm

## STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Thickness	5.4 mils	0.13 mm
Elongation	9 %	9 %
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## APPLICABLE STANDARDS

ASTM D6123/D6123M-07 Type I

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.