

PACKAGING & SPLICING KRAFT FLATBACK PAPER TAPE

TYPICAL APPLICATIONS

- Hand and machine carton sealing
- Splicing of various substrates
- General purpose packaging, binding, holding, tabbing, reinforcing, banding and patching tape for a variety of substrates

ADVANTAGES AND BENEFITS

- Strong, flexible and conformable backing
- High cross-directional tensile strength
- Aggressive, high tack adhesive with excellent holding power
- Tape color blends well with kraft cartons
- Resists curling, abrasion and water
- Meets FDA specifications for indirect food contact

CONSTRUCTION

Overall Grade/Function: General Purpose
 Backing: Extensible, kraft, flatback paper
 Adhesive: High tack, thermoplastic rubber

COLOR(S)



Kraft (KFT)

STANDARD WIDTH(S)

24 mm 36 mm 48 mm 72 mm 4 in 5 in

Contact your Shurtape sales representative for other available sizes.

STANDARD LENGTH(S)

60 yd 55 m



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength (Machine Direction)	33 lbs/in width	57.8 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	6.1 mils	0.15 mm
Elongation	5%	5%
Service Temperature Range	60 F to 150 F	16 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A-883B, Type II, ASTM D6123/D6123M-07, Type II; FDA Indirect Contact 21 CFR - 174.5, 175.105, 176.170 & 176.180

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC
 Form# TDS-FP-97-09/11/2013