

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health
Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (<i>As Used on Label and List</i>) TF 1650	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name IMG	Emergency Telephone Number 714-771-2401
Address (<i>Number, Street, City, State, and ZIP Code</i>) 1740 W. Katella Ave. Suite A Orange, CA 92867	Telephone Number for information 714-771-2401 Date prepared Nov 1, 2012 Signature of Preparer (<i>optional</i>)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(<i>optional</i>)
Fibrous glass CAS: 14808-60-7 10 mg/m ³ of air for fiber				
Diameters of less than 7 microns				
Polytetrafluoroethylene CAS: 9002-84-0 N/A				

Section III - Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	1.6
Vapor Pressure (mm Hg)	N/A	Melting Point	>400°F
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water @ 20 degree C - Insoluble			
Appearance and Odor Gray one side/brown other side No Odor			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) >250°C by TOC	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media: Carbon dioxide, water, or dry chemical			
Special Fire Fighting Procedures: Does not burn without an external source of fuel under normal conditions. Will burn in an atmosphere containing in excess of 98% oxygen if an ignition source is present.			
Unusual Fire Explosion Hazards: In an extreme fire situation, protection from hydrogen fluoride fumes should be employed.			
.			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Stability N/A	Unstable		Conditions to Avoid: Temperatures above 250°C
	Stable	X	
Incompatibility (Materials to Avoid) Strong oxidizing agents			
Hazardous Decomposition or Byproducts: Hydrogen fluoride, carbon monoxide, carbon dioxide			
Hazardous Polymerization	May Occur		Conditions to Avoid None
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
This material will not enter the body during normal use.	N/A	N/A	N/A
Carcinogenicity: Non - Carcinogenic	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure: None Known			
Medical Conditions Generally Aggravated by Exposure : None Known			
Emergency and First Aid Procedures: Wash with soap and			

water after handling; toxic gaseous materials may evolve at temperatures above 250°C; if inhaled, remove person to fresh air.			
Toxicological Data:			
No Known Risk			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Material is a solid.
Waste materials identification code: N/A
Waste Disposal Method Burial in federal or state approved landfill.
Precautions to Be taken in Handling and Storing: None Known
Storage: No Special Conditions
Other Precautions: None Known

Section VIII - Control Measures

Respiratory Protection (Specify Type)		
Ventilation	Local Exhaust N/A	Special N/A
	Mechanical (General N/A	Other None known

Protective Gloves	Eye Protection
-------------------	----------------

N/A	N/A
Other Protective Clothing or Equipment None Known	
Work/Hygienic Practices: Wash with soap and water after handling.	