

# AEROCEL®

## AEROCOAT



# AEROCOAT

Pure Acrylic Emulsion Paint  
For **AEROCEL**® Insulations

# AEROCEL<sup>®</sup>

## Aerocoat

### Pure Acrylic Emulsion Paint For Aerocel Insulation Products



**Aerocel Aerocoat** is a pure acrylic emulsion water based latex paint especially designed for use with Aerocel insulation products. **Aerocel Aerocoat** has superb properties that help protect against ultraviolet rays and other adverse weather conditions.

**Aerocel Aerocoat** having elongation properties of over 400% promotes superior adhesion. Aerocel coating is effective as a protective coating or decorative coating for Aerocel insulation products and provides a smoothing aesthetic appearance that lasts for many years. **Aerocel Aerocoat** is supplied in quarts and gallons and is available in black or white.

#### Application

Stir thoroughly before applying with brush or roller. All surfaces to be coated must be thoroughly clean, free from oil, grease or other contaminants. Where a surface has been previously coated, remove as much of the old coating as possible before applying **Aerocel Aerocoat**. Where coating is required, it is recommended that 2 coats be applied. Allow 3 to 4 hours

drying time before second coat is applied. No primer is required. One gallon will cover up to 400 sq. ft.

**Aerocel Aerocoat** can be diluted using clean water at a rate not to exceed 10% by volume.

#### Precaution

Non flammable and non toxic. Close cover tightly after use. Mix **Aerocel Aerocoat** with water in accordance to amount needed. Avoid mixing more than required as it is not advisable to store **Aerocel Aerocoat** that is mixed with water more than 5 days. Keep out of the reach of children.

#### Physical Properties

**Composition:** Selected 100% acrylic emulsion paint

**Net Weight:** Approximately 10#/gal. 2.5#/qt.

**Solids:** Approximately 50% by weight

**Viscosity:** Thick smooth consistency for easy application

**Application:** Brush or roller

**Coverage:** Up to 400 sq. ft./gal

**Shelf life:** One year. Store at room temperature. Avoid freezing.

**Drying time:** Three to four hours for second coat.

**Container size:** Quarts and Gallons

**Flammability:** Water base, not flammable



9051 Executive Park Drive • Suite 400 • Knoxville, Tennessee 37923  
Telephone: 865-690-5740 • Fax: 865-690-5695 • Toll Free: (866) AEROCEL  
[www.aeroflexusa.com](http://www.aeroflexusa.com)