




## Utility Grade Duct Tape



- Backing:** PE Coated Cloth
- Adhesive:** Rubber
- Liner:** N/A
- Colors:** Silver, Black
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 48mm x 55m, 72mm x 55m

### Applications

- Maintenance & general repair
- Joint sealing & pipe wrapping
- Bundling, patching & mending
- Heavy-duty box sealing

### Features

- PE-Coated Cloth Backing
- Natural rubber based adhesive
- Low VOC Content

### Benefits

- Conformable & hand tearable
- Resists Twisting & curling
- Bonds well to most surfaces, good all climate performance
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	7 mils	177.8 mic	ASTM D-1000
<b>Adhesion to Steel</b>	65 oz/in	7.2 N/cm	PSTC-101
<b>Adhesion to Backing</b>	38 oz/in	4.3 N/cm	PSTC-101
<b>Tensile Strength</b>	22 lb/in	38.5 N/cm	ASTM D-1000
<b>Elongation</b>	19%		ASTM D-1000
<b>Operating Temperature</b>	40-200°F	4-93°C	
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F  
 Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.