

SPECIFICATIONS

This product is a combination metal and paper wallboard cornerbead tape that is used in conjunction with a joint compound to conceal inside and outside corners in drywall construction.

The product consist of 2" wide aluminum bonded 100% to unperforated, unsparked paper tape with moisture and alkali resistant adhesive.



Material Metal:

1 piece 2" wide scored annealed aluminum x .016" thickness with a clean neutral surface to allow adhesion on both sides.

Paper Tape:

Paper backing is 4½" wide.

Packaging:

Packaged 100 ft. per box, weight 5 lbs. per box.

Certification:

Product conforms to ASTM B 209 standards.

Physical Analysis

Mill Finish	.0162 gauge aluminium
Tensile strength - PSI	21,500
Yield strength - PSI	20,100
Elongation	8.5%

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



Innovative Insulation Systems

HEADQUARTERS:

6810 Cochran Road | Solon, OH 44139 | 440.914.1122 | 440.914.1133 Fax | 1.800.874.1748

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon, OH 44139 | 440.914.1122

North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

California: 4283 Pock Lane #200 | Stockton, CA 95206 | 1.800.833.4500

Texas: 8905 Market Street | Houston, TX 77029 | 1.800.874.1748