

### DESCRIPTION

ITW Aluminum Deep Corrugated Sheets are available in two different nominal corrugation profiles, with bare or painted exterior surface, and in smooth or stucco embossed surface finishes. The corrugation profiles are engineered to provide strength and stiffness superior to that of standard aluminum jacketing. The dimensions of the two corrugation profiles are shown in the diagram to the right.

Aluminum Deep Corrugated Sheets are a premier protective outer surface for mechanical insulation systems on flat surfaces, equipment, towers, vessels, and vertical cylindrical tanks with an outer diameter larger than 8 ft. ITW Aluminum Deep Corrugated Sheets protect the insulation and underlying surface from physical damage, UV exposure, corrosive atmospheres, and water.

### COMPOSITION

ITW Aluminum Deep Corrugated Sheets are typically manufactured using alloys 3105 or 3003 which have very similar composition and performance and are considered interchangeable for use as insulation jacketing. For more information on these aluminum alloys, see the ITW Aluminum Roll Jacketing data sheet. ITW reserves the right to ship whichever alloy is in stock at the time of order placement. One of these two specific alloys or an alternative alloy can be specified by purchaser at time of order placement but this may affect minimum quantity, lead-time, and price.

### DIMENSIONS

Standard dimensions for ITW Deep Corrugated Sheets are:

Width = nominal 33 inches<sup>1</sup>

Length = 8, 10, and 12 feet<sup>2</sup>

Number of Peaks / Nominal Coverage<sup>3</sup>

1-1/4" Sheet = 25 (26 in Canada) / 31-3/4"

2-1/2" Sheet = 12 (13 in Canada) / 30-1/2"


<sup>1</sup>The actual width will vary slightly from the nominal width based on gauge and other manufacturing variables.

<sup>2</sup>Custom lengths from 4 to 12 ft can be specified by purchaser at time of order placement but this may affect minimum quantity and lead-time.


<sup>3</sup>Coverage is the effective horizontal distance covered by each sheet and is less than the sheet width because of the need to overlap neighboring sheets by a minimum of one corrugation. Note that coverage is nominal and will vary based on gauge, and other manufacturing variables.



#### 1-1/4" Deep Corrugated



#### 2-1/2" Deep Corrugated



### COMPLIANCE TO STANDARDS

All bare and painted Aluminum Deep Corrugated Sheets from ITW Insulation Systems comply with the requirements of ASTM C1729 (Aluminum Jacketing Material Standard) which includes the strength and chemical composition requirements for compliance to ASTM B209 (Aluminum Alloy Standard).

### THICKNESS

ITW Aluminum Deep Corrugated Sheets are available in standard thicknesses of 0.016", 0.020", 0.024", 0.032" and 0.040 inches.

2-1/2" deep corrugated sheet is best suited for thicker gauges. ITW recommends that 2-1/2" profile deep corrugated sheet be used with a minimum thickness/gauge of 0.024".

## POLYSURLYN MOISTURE BARRIER

ITW Aluminum Deep Corrugated Sheets come standard with a Polysurlyn Moisture Barrier (PSMB) on the interior surface. PSMB is an engineered three layer coextruded film of polyethylene and Surlyn\* polymers with a total film thickness of 3 mils (76 µm) that is heat laminated in the factory to the interior surface of aluminum jacketing. ITW recommends the use of PSMB on all aluminum jacketing to help prevent pitting, crevice, and galvanic corrosion of the interior surface of the metal jacketing and the insulated pipe, tank, or equipment.

Due to its superior performance characteristics, PSMB replaces the old moisture barrier technology of 1 to 3 mil thick polykraft.

## RECOMMENDED USES

ITW Aluminum Deep Corrugated Sheets are recommended for use over the insulation on flat surfaces, equipment, towers, vessels, and vertical cylindrical tanks with an outer diameter larger than 8 ft. Examples of where ITW Deep Corrugated Sheets are the preferred jacketing are distillation columns, tank farms, fractionation units, cokers, chemical storage tanks, breechings, large ducts, wastewater and sewage storage tanks and large vertical ammonia storage tanks.

## LIMITATIONS ON USE

ITW Aluminum Deep Corrugated Sheets are not appropriate for the following applications:

- For large flat surfaces such as boiler walls and precipitators, ITW Box Rib Sheets are recommended
- For applications requiring deep corrugated sheet where a maximum resistance to fire or where maximum resistance to corrosion is required, ITW Stainless Steel Deep Corrugated Sheets should be used

## SURFACE FINISH

ITW Deep Corrugated Sheets are available in smooth or stucco embossed finish. For more information on these finishes see the ITW Aluminum Roll Jacketing data sheet.

ITW Deep Corrugated Sheets are available with a painted outer surface. For more information on this see the ITW Painted Aluminum Roll Jacketing data sheet.

## EMITTANCE OF DEEP CORRUGATED

ITW Aluminum Deep Corrugated Sheet has a surface emittance as measured by ASTM C1371 of:

- Bare aluminum = 0.1 (oxidized in service)
- Painted, all colors except clear = 0.8
- Painted with clear coating = 0.5

## FLAMMABILITY

ITW Aluminum Jacketing with a 3 mil polysurlyn moisture barrier has been tested for flammability using the industry standard ASTM E84 test method. The results are shown below. ITW would expect Deep Corrugated Sheet to have equivalent flammability performance since it is the same material just produced with a corrugated profile.

ASTM E84 Flame Spread Index = 0

ASTM E84 Smoke Developed Index = 5

(Tested with exterior metal surface exposed to the flame)

## FIT AND INSTALLATION

When ordering replacement ITW Deep Corrugated Sheets for an existing installation consult the ITW Deep Corrugated Sheet Fit and Measurements data sheet or your ITW sales representative for the information required to best assure fit.

Installation procedures for deep corrugated sheet are available in the National Commercial and Industrial Insulation Standards published by the Midwest Insulation Contractors Association (MICA Manual).

## SEALING OF JOINTS

The joints between neighboring pieces of deep corrugated sheet are not typically sealed. If the specifier wants a more water tight seal, the vertically oriented overlap joint between deep corrugated pieces horizontally adjacent to one another can be sealed with an appropriate joint sealant. This should be applied between the overlapping pieces of metal in the joint and not as a caulking bead on the exterior lip of the joint.