



SILVERJAC™ 1700 Insulation Jacketing Material

SILICONE/FIBERGLASS COMPOSITES ENGINEERED FOR REMOVABLE INSULATION SERVICE

SILVERJAC™ 1700 Description:

This silicone/fiberglass composite with a proven flexible coating is engineered for standard duty insulation jacketing applications.

- **Successfully used in insulation jacketing service since 1985**
- **Incorporates proven SILVERJAC™ coating technology**
- **Severe chemical and temperature exposure capabilities**
- **Variations available upon request**



- **Flame-resistant**
- **Easily sewn**

SILVERJAC™ 1700 PROPERTIES

Upper Use Temperature:	480°F (249°C) Continuous Service
Weight:	17.0 oz/yd ² (557 g/m ²)
Thickness:	0.017" (0.43 mm)
Width:	60" (1524 mm) Nominal
Tensile Strength (Warp):	370 lbs/in (3240 N/50 mm)
Tensile Strength (Fill):	310 lbs/in (2714 N/50 mm)

Silverjac™ is a trademark of TEXTILES COATED INTERNATIONAL. Patents worldwide. This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High Performance PTFE Composites and Laminates