



# TUFJAC™ 1550 Insulation Jacketing Material

SILICONE/FIBERGLASS COMPOSITES ENGINEERED FOR REMOVABLE INSULATION SERVICE

## TUFJAC™ 1550 Description:

This lightweight silicone/fiberglass composite has a rugged coating that is engineered for removable pads, flanges, and valve covers.

- **Successfully used in insulation jacketing service since 1985**
- **Incorporates rugged TUFJAC™ coating technology**
- **Severe chemical and temperature exposure capabilities**
- **Variations available upon request**



- **Flame-resistant**
- **Easily sewn**

## TUFJAC™ 1550 PROPERTIES

<b>Upper Use Temperature:</b>	480°F (249°C) Continuous Service
<b>Weight:</b>	15.5 oz/yd <sup>2</sup> (526 g/m <sup>2</sup> )
<b>Thickness:</b>	0.016" (0.41 mm)
<b>Width:</b>	60" (1524 mm) Nominal
<b>Tensile Strength (Warp):</b>	370 lbs/in (3240 N/50 mm)
<b>Tensile Strength (Fill):</b>	310 lbs/in (2714 N/50 mm)

TUFJAC™ is a trademark of TEXTILES COATED INTERNATIONAL. Patents worldwide. This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High Performance PTFE Composites and Laminates

200 Bouchard Street, Manchester, NH 03103

PHONE: (603) 296-2221

FAX: (603) 296-2248

www.textilescoated.com